

# LEITZ PRIME



Leitz Cine GmbH  
Am Leitz-Park 2 | 35578 Wetzlar | Germany  
[www.leitz-cine.com](http://www.leitz-cine.com) | [cc@leitz-cine.com](mailto:cc@leitz-cine.com)

All information subject to change



# LEITZ PRIME

## TECHNICAL SPECIFICATIONS

Focal Length (mm)	18	21	25	29	35	40	50	65	75	100	135	180	350
Aperture	T1.8											T2	T3.6
Image Circle	46.5 mm												
Close Focus (ft)	1'2"	1'10"	1'10"	1'2"	1'6"	1'2"	1'7"	2'2"	2'6"	3'11"	3'11"	4'11"	9'10"
Close Focus (m)	0.35	0.55	0.55	0.35	0.45	0.35	0.47	0.65	0.75	1.2	1.2	1.5	3
Horizontal angle of view "Full Frame" 36 mm x 24 mm	90.0°	81.2°	71.5°	63.7°	54.4°	48.5°	39.6	31.0°	27.0°	20.4°	15.2°	11.4°	5.9°
Horizontal angle of view "Super 35" 24.9 mm x 18.7 mm	69.3°	61.3°	52.9°	46.5°	39.1°	34.6°	28.0°	21.7°	18.8°	14.2°	10.5°	7.9°	4.1°
Weight (lb)	7.1	6.1	6.2	5.9	6.3	6.0	6.0	6.1	6.2	6.1	6.4	6.8	9.7
Weight (kg)	3.2	2.76	2.8	2.67	2.87	2.71	2.7	2.78	2.83	2.77	2.89	3.1	4.4
Length (in / mm)	7.9" / 201.5	7.2" / 183.7										7.9" / 201.5	12.5" / 317



Lens Mount	PL, LPL with Cooke/i
Front Diameter	114 mm
Front Filter   Rear Filter	M 112 mm x 1.5 mm screw-in   Via net holder
Matched Focus/Iris Ring Locations	All focal lengths
Focus Rotation   Iris Rotation	270° (except 18 mm 207°)   66° (except 18 mm 63°; 350 mm 49°)
Focus Scales	Turnable scales, easy change from imperial to metric
Iris Blades   Iris Shape	15 Blades (except 350 mm 21 Blades)   Circular through all stops
Color Matching	Matched with LEITZ ZOOM lenses