

LEITZ ZOOM



Leitz Cine GmbH
Am Leitz-Park 2 | 35578 Wetzlar | Germany
www.leitz-cine.com | cc@leitz-cine.com

规格如有更改恕不另行通知



LEITZ ZOOM

技术参数

焦段 (mm)	25-75		55-125	
变焦倍数	3		2.3	
最大光圈	T 2.8			
成像圈	46.5 mm			
最近焦 (尺)	3'		3'5"	
最近焦 (米)	0.91		1.05	
水平视角 “全画幅” 36 x 24 mm	at 25 mm	71.5°	at 55 mm	36.2°
	at 50 mm	39.6°	at 90 mm	22.6°
	at 75 mm	27°	at 125 mm	16.4°
水平视角 “超 35” 24.9 x 18.7 mm	at 25 mm	52.9°	at 55 mm	25.5°
	at 50 mm	28°	at 90 mm	15.7°
	at 75 mm	18.8°	at 125 mm	11.4°
重量(磅)	8.2		9.7	
重量(公斤)	3.7		4.4	
长度(吋)	10.5		11.02	
长度 (mm)	266.6		279.9	
入射光孔位置 (mm) <small>朝向机器 对焦无限远</small>	at 25 mm	268.7	at 55 mm	238.1
	at 50 mm	266	at 90 mm	199.8
	at 75 mm	258.7	at 125 mm	179.6
变焦环幅度	112.65°		120°	
光圈叶片	15		21	



卡口	PL, LPL 帶 Cooke/i 触点
前口直径	114 mm
前口滤片	M 112 x 1.5 mm 螺纹
后滤片	后滤片环 (27 mm - 75 mm PL 口不設后滤片环)
光圈/焦点环距离	两颗变焦皆一致
对焦环幅度	270°
光圈环幅度	54°
对焦环刻度	尺/米互换
光圈形状	各级恒定圆形
色温	匹配 LEITZ PRIME 定焦頭